

MATERIAL SAFETY DATA SHEET

Trade Name: Johnsen's Automatic Transmission Fluid 7 oz
MSDS NO. 2512-8
Revision Date: 08/14/2007
Date Printed: 01/20/2009

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade Name: Johnsen's Automatic Transmission Fluid 7 oz
Chemical Family: Petroleum Oil Blend
Synonyms: None
Emergency Telephone (24 hr.): CHEMTREC 1-800-424-9300
Supplier: Technical Chemical Company, P.O. Box 139, Cleburne, Texas 76033

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight %	OSHA TWA	OSHA STEL	OSHA SKIN
Lubricating Oil 64742-52-5	68-73	Not Listed	Not Listed	Not Listed
500 Vis. Refrigeration Oil 64742525	15-19	Not Listed	Not Listed	Not Listed
Lubrizol 9636H	11-13	Not Listed	Not Listed	Not Listed

Component	Weight %	OSHA Z PEL	OSHA Z TWA	OSHA Z Ceiling
Lubricating Oil 64742-52-5	68-73	2000 mg/m ³ 500 ppm	1600 mg/m ³ 400 ppm	Not Listed
500 Vis. Refrigeration Oil 64742525	15-19	Not Listed	Not Listed	Not Listed
Lubrizol 9636H	11-13	Not Listed	Not Listed	Not Listed

Component	ACGIH TLV TWA	ACGIH TLV STEL	ACGIH TLV Ceiling
Lubricating Oil 64742-52-5	Not Listed	Not Listed	Not Listed
500 Vis. Refrigeration Oil 64742525	Not Listed	Not Listed	Not Listed
Lubrizol 9636H	Not Listed	Not Listed	Not Listed

3. HAZARDS IDENTIFICATION

Emergency Overview: May irritate the eyes. May irritate the skin. Possible redness and defatting may result from prolonged skin exposure to this material. Avoid breathing oil mist.

HMIS Classification: Health: 1 Flammability: 1 Physical Hazard: 0
NFPA Rating: Health: 1 Flammability: 1 Reactivity: 0

4. FIRST AID MEASURES

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower lids. Seek medical attention if irritation persists.

Ingestion: If swallowed, do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person. If vomiting occurs, keep head lower than hips to prevent aspiration.

Inhalation: If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin Contact: Wash with soap and water. Remove contaminated clothing and shoes, and launder before reuse. If irritation persists or signs of toxicity occur, seek medical attention. If product is injected into or under the skin, or into any part of the body, the individual should be evaluated immediately by a physician as a surgical emergency.

MATERIAL SAFETY DATA SHEET

Trade Name: Johnsen's Automatic Transmission Fluid 7 oz
MSDS NO. 2512-8
Revision Date: 08/14/2007
Date Printed: 01/20/2009

5. FIRE FIGHTING MEASURES

Flammable Properties

Flash Point F(°C): >410-440 F
Flash Point Method: TAG Closed Cup
Flammable Limits in Air - Lower (%): Not Determined
Flammable Limits in Air - Upper (%): Not Determined
Autoignition Temperature F(°C): Not Determined
Extinguishing Media: Foam. Water. Dry chemical. Carbon dioxide. Water fog. Use water spray to keep containers cool that are exposed to heat or flames.

Protection Of Fire-Fighters:

Special Fire-Fighting Procedures: Wear approved positive-pressure self-contained breathing apparatus and protective clothing.
Hazardous Combustion Products: Oxides of carbon, nitrogen and phosphorus. Hydrogen Sulfide.
Aerosol Comments: Not Applicable

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear appropriate protective clothing and equipment to prevent skin and eye contact.
Spill Procedures: Contain any liquid from leaking containers.
Action to be taken if material is released or spilled: Wear proper protective equipment as specified in the protective equipment section. Remove sources of ignition. Increase area ventilation. Absorb spills on inert material such as perlite, vermiculite, sand or dirt. Place in double polyethylene bags. Isolate from other waste materials.
Environmental Precautions: Do not allow to enter sanitary drains, sewer or surface and subsurface waters.

7. HANDLING AND STORAGE

Handling and Storage: Keep container closed when not in use. Avoid breathing vapors, if exposed to high vapor concentration, leave area at once. Avoid contact with skin and eyes. Use only in a well ventilated area. Keep away from food and smoking materials. Wash hands before eating and smoking.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Showers. Eyewash stations. Use local exhaust.
Eyes: Wear safety glasses or goggles to protect against exposure.
Skin Protection: Use chemical resistant gloves for prolonged skin contact. Wash hands and other exposed areas with mild soap and water before eating, drinking, smoking and when leaving work.
Respiratory Protection: Appropriate respiratory protection shall be worn when applied engineering controls are not adequate to protect against inhalation exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear red liquid.
Odor: MILD PETROLEUM
pH Value: Not Determined
Vapor Pressure: >1 mm Hg
Vapor Density (Air=1): Not Determined
Boiling Point (°F): Not Determined.
Melting/Freezing Point: Not Determined.
Solubility in Water: SLIGHT
Bulk Density at 20°C: Not Determined
Molecular Weight: Mixture
Specific Gravity (H2O=1): 1.0 @ 60 F
Viscosity: Not Determined.
Evaporation Rate: Not Determined
VOC Content(%): 12.21 (CARB Method 310)
Decomposition Temperature: Not Known

10. STABILITY AND REACTIVITY

Chemical Stability: STABLE.
Conditions to Avoid: None anticipated
Materials to Avoid: Oxidizing agents.

MATERIAL SAFETY DATA SHEET

Trade Name: Johnsen's Automatic Transmission Fluid 7 oz
MSDS NO. 2512-8
Revision Date: 08/14/2007
Date Printed: 01/20/2009

10. STABILITY AND REACTIVITY

Hazardous Decomposition Products: Oxides of carbon. Oxides of nitrogen. Oxides of phosphorus. Hydrogen sulfide
Hazardous Polymerization: WILL NOT OCCUR

11. TOXICOLOGICAL INFORMATION

Toxicological Data:

Component	Route	Species	Dose
Lubricating Oil 64742-52-5	NA	NA	Not known.
500 Vis. Refrigeration Oil 64742525	Inhalation	Rats	Not known.
Lubrizol 9636H	Inhalation	Rats	Not known.

Carcinogenicity:

Component	IARC	NTP	OSHA
Lubricating Oil 64742-52-5	Not Listed	Not Listed	Not Listed
500 Vis. Refrigeration Oil 64742525	Not Listed	Not Listed	Not Listed
Lubrizol 9636H	Not Listed	Not Listed	Not Listed

12. ECOLOGICAL INFORMATION

Remarks: Ecological testing has not been conducted on this product.

13. DISPOSAL CONSIDERATION

Waste Classification: If disposed of, this material may be hazardous for disposal under RCRA due to reactivity.
Waste Management: Not determined.
Disposal Method: Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORTATION INFORMATION

U.S. DOT:

Proper Shipping Name: Not Regulated
Hazard Class: Not Regulated
UN/NA Number: Not Applicable
DOT Packing Group: Not Applicable

IMDG:

Proper Shipping Name: Not Regulated
Hazard Class: Not Regulated
Hazard Subclass: Not determined.
UN No.: Not Applicable
Packing Group: Not Applicable
Marine Pollutant: No

15. REGULATORY INFORMATION

US Federal Regulations:

MATERIAL SAFETY DATA SHEET

Trade Name: Johnsen's Automatic Transmission Fluid 7 oz
 MSDS NO. 2512-8
 Revision Date: 08/14/2007
 Date Printed 01/20/2009

Component	SARA 313	SARA 302	TPQ	RQ
Lubricating Oil 64742-52-5	Not Listed	Not Listed	Not Listed	Not Listed
500 Vis. Refrigeration Oil 64742525	Not Listed	Not Listed	Not Listed	Not Listed
Lubrizol 9636H	Not Listed	Not Listed	Not Listed	Not Listed

SARA 311/312 Hazard Categories: Not Determined.

State Regulations:

Component	California Prop. 65 Cancer list	California - Prop 65 Developmental Toxicity	California Prop. 65 Reproductive Female	California Prop. 65 Reproductive Male
Lubricating Oil 64742-52-5	Not Listed	Not Listed	Not Listed	Not Listed
500 Vis. Refrigeration Oil 64742525	Not Listed	Not Listed	Not Listed	Not Listed
Lubrizol 9636H	Not Listed	Not Listed	Not Listed	Not Listed

U.S. TSCA: One or more components of this product is not listed on the TSCA Inventory.
Canadian Inventory: One or more components of this product is not listed on the Canadian DSL or NDSL Inventory.

Consumer Product Safety Improvement Act of 2008 General Conformity Certification

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product container.

16. OTHER INFORMATION

General Notes:
Disclaimer:

Do not allow undiluted material or large quantities to reach groundwater, bodies of water or sewer system. The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.