

MATERIAL SAFETY DATA SHEET

Trade Name: Johnsens QFF w/Cone
MSDS NO. 3850
Revision Date: 04/11/2006
Date Printed: 12/30/2008

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade Name: Johnsens QFF w/Cone
Chemical Family: LATEX ACRYLIC
Synonyms: None
Emergency Telephone (24 hr.): 24-Hour Emergency Information: CHEMTREC (800) 424-9300

Supplier: Technical Chemical Company, P.O. Box 139, Cleburne, Texas 76033

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight %	OSHA TWA	OSHA STEL	OSHA SKIN
Propane 74-98-6	10-20	Not Listed	Not Listed	Not Listed
Iso-Butane 75-28-5	5-15	Not Listed	Not Listed	Not Listed
DOT 3 Brake Fluid NA	2-5	Not Listed	Not Listed	Not Listed
Sodium nitrite 7632-00-0	.01-.5	Not Listed	Not Listed	Not Listed

Component	Weight %	OSHA Z PEL	OSHA Z TWA	OSHA Z Ceiling
Propane 74-98-6	10-20	1800 mg/m ³ 1000 ppm	1800 mg/m ³ 1000 ppm	Not Listed
Iso-Butane 75-28-5	5-15	Not Listed	Not Listed	Not Listed
DOT 3 Brake Fluid NA	2-5	Not Listed	Not Listed	Not Listed
Sodium nitrite 7632-00-0	.01-.5	Not Listed	Not Listed	Not Listed

Component	ACGIH TLV TWA	ACGIH TLV STEL	ACGIH TLV Ceiling
Propane 74-98-6	1000 ppm	Not Listed	Not Listed
Iso-Butane 75-28-5	1000 ppm	Not Listed	Not Listed
DOT 3 Brake Fluid NA	Not Listed	Not Listed	Not Listed
Sodium nitrite 7632-00-0	Not Listed	Not Listed	Not Listed

3. HAZARDS IDENTIFICATION

Emergency Overview: Warning: Extremely Flammable. Content under pressure. Keep away from heat, sparks and flame. May irritate the eyes. May irritate the skin.

HMIS Classification: Health: 2 Flammability: 4 Physical Hazard: 2
NFPA Rating: Health: 3 Flammability: 4 Reactivity: 0

4. FIRST AID MEASURES

MATERIAL SAFETY DATA SHEET

Trade Name: Johnsens QFF w/Cone
MSDS NO. 3850
Revision Date: 04/11/2006
Date Printed: 12/30/2008

4. FIRST AID MEASURES

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower lids. Seek medical attention if irritation persists.

Ingestion: If swallowed, do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person. Get medical attention! If vomiting occurs, keep head lower than hips to prevent aspiration.

Inhalation: If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin Contact: Wash with soap and water for 15 minutes. If irritation persists or signs of toxicity occur, seek medical attention. Remove contaminated clothing and shoes, and launder before reuse.

5. FIRE FIGHTING MEASURES

Flammable Properties

Flash Point °F(°C): -200 F (lowest Component)
Flash Point Method: TAG Closed Cup
Flammable Limits in Air - Lower (%): 1.8% (Lowest Component)
Flammable Limits in Air - Upper (%): 8.4% (Lowest Component)
Autoignition Temperature °F(°C): Not Determined
Extinguishing Media: Dry chemical. Carbon dioxide. Use water spray to keep containers cool that are exposed to heat or flames. Water fog.

Protection Of Fire-Fighters:

Special Fire-Fighting Procedures: Wear approved positive-pressure self-contained breathing apparatus and protective clothing. Vapor may cause flash fire.

Hazardous Combustion Products: Carbon Dioxide. Carbon Monoxide. Fumes and Smoke.
Aerosol Comments: NFPA Level 1 Aerosol

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear appropriate protective clothing and equipment to prevent skin and eye contact.

Spill Procedures: Contain any liquid from leaking containers. Avoid all sources of ignition; heat, sparks and open flames.

Action to be taken if material is released or spilled: Do not puncture or incinerate container. Contents under pressure. Wear proper protective equipment as specified in the protective equipment section. Remove sources of ignition. Leaking containers should be removed to an isolated, well-ventilated area and transferred to other suitable containers. Wipe, scrape, or soak up in an inert material and put in a container intended for flammable materials for disposal.

Environmental Precautions: Do not allow to enter sanitary drains, sewer or surface and subsurface waters. Keep out of lakes, ponds or streams.

7. HANDLING AND STORAGE

Handling and Storage: Caution: Contents under pressure. Keep away from heat and open flame. Use only in a well ventilated area. Avoid breathing vapors, if exposed to high vapor concentration, leave area at once. Avoid contact with skin and eyes. Do not puncture, incinerate or store above 120 F. Exposure to high temperatures may cause bursting. DO NOT store in the passenger compartment of an automobile.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Use in a well ventilated area. Local exhaust ventilation as necessary to maintain exposures to within applicable limits.

Eyes: Chemical goggles; also wear a face shield if splashing hazard exists.

Skin Protection: Avoid skin contact. Wear protective clothing and gloves.

Respiratory Protection: Do not breath mist or vapor. Use in a well ventilated area. Appropriate respiratory protection shall be worn when applied engineering controls are not adequate to protect against inhalation exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: White foam or liquid.
Odor: SOLVENT
pH Value: Not Determined

MATERIAL SAFETY DATA SHEET

Trade Name: Johnsens QFF w/Cone
MSDS NO. 3850
Revision Date: 04/11/2006
Date Printed: 12/30/2008

9. PHYSICAL AND CHEMICAL PROPERTIES

Vapor Pressure: 400 @ 760 mm Hg
Vapor Density (Air=1): 2.0
Boiling Point (°F): 133 F. (Liquid)
Melting/Freezing Point: Not Determined.
Solubility in Water: SOLUBLE
Bulk Density at 20°C: approx. 6.58 lb/gal (Liquid)
Molecular Weight: Mixture
Specific Gravity (H2O=1): .79 @ 60 F (liquid)
Viscosity: Not Determined.
Evaporation Rate: 7.7 (BuAc=1)
VOC Content(%): Not Determined.
Decomposition Temperature: Not Determined

10. STABILITY AND REACTIVITY

Chemical Stability: STABLE.
Conditions to Avoid: Keep away from heat, sparks and flame. Avoid any source of ignition. Do not expose to heat or store at temperatures above 120 F.
Materials to Avoid: Contact with oxidizing agents. Strong bases. Strong acids. Chlorine compounds. Chloroform. Alkalis. Potassium t-butoxide. Chromic anhydride, lead perchlorate and perchloric acids.
Hazardous Decomposition Products: Carbon monoxide. Carbon dioxide.
Hazardous Polymerization: WILL NOT OCCUR

11. TOXICOLOGICAL INFORMATION

Toxicological Data:

Component	Route	Species	Dose
Propane 74-98-6	NA	NA	Not known.
Iso-Butane 75-28-5	Inhalation	Rats	LC50 57 pph/15M
DOT 3 Brake Fluid NA	Oral	Rats	LD50 2000 mg/kg
Sodium nitrite 7632-00-0	Inhalation	Rats	LC50 5500 ug/m ³ /4H

Carcinogenicity:

Component	IARC	NTP	OSHA
Propane 74-98-6	Not Listed	Not Listed	Not Listed
Iso-Butane 75-28-5	Not Listed	Not Listed	Not Listed
DOT 3 Brake Fluid NA	Not Listed	Not Listed	Not Listed
Sodium nitrite 7632-00-0	Not Listed	Not Listed	Not Listed

12. ECOLOGICAL INFORMATION

Remarks: Ecological testing has not been conducted on this product.

13. DISPOSAL CONSIDERATION

Waste Classification: Not determined.

MATERIAL SAFETY DATA SHEET

Trade Name: Johnsens QFF w/Cone
 MSDS NO. 3850
 Revision Date: 04/11/2006
 Date Printed: 12/30/2008

13. DISPOSAL CONSIDERATION

Waste Management: Not determined.
Disposal Method: Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORTATION INFORMATION

U.S. DOT:
Proper Shipping Name: CONSUMER COMMODITY
Hazard Class: ORM-D
UN/NA Number: Not Applicable
DOT Packing Group: Not Applicable

IMDG:
Proper Shipping Name: Aerosols (Limited Quantity)
Hazard Class: 2.0
Hazard Subclass: Not determined.
UN No.: UN1950
Packing Group: PG II
Marine Pollutant: No

15. REGULATORY INFORMATION

US Federal Regulations:

Component	SARA 313	SARA 302	TPQ	RQ
Propane 74-98-6	Not Listed	Not Listed	Not Listed	Not Listed
Iso-Butane 75-28-5	Not Listed	Not Listed	Not Listed	Not Listed
DOT 3 Brake Fluid NA	Not Listed	Not Listed	Not Listed	Not Listed
Sodium nitrite 7632-00-0	Listed.	Not Listed	Not Listed	Not Listed

US OSHA HEALTH CLASSIFICATION: Hazardous per OSHA 29 CFR 1910.1200
SARA 311/312 Hazard Categories: Not Determined.

State Regulations:

Component	California Prop. 65 Cancer list	California - Prop 65 Developmental Toxicity	California Prop. 65 Reproductive Female	California Prop. 65 Reproductive Male
Propane 74-98-6	Not Listed	Not Listed	Not Listed	Not Listed
Iso-Butane 75-28-5	Not Listed	Not Listed	Not Listed	Not Listed
DOT 3 Brake Fluid NA	Not Listed	Not Listed	Not Listed	Not Listed
Sodium nitrite 7632-00-0	Not Listed	Not Listed	Not Listed	Not Listed

MATERIAL SAFETY DATA SHEET

Trade Name: Johnsens QFF w/Cone
MSDS NO. 3850
Revision Date: 04/11/2006
Date Printed: 12/30/2008

Component	New Jersey Right-to-Know List:
Propane 74-98-6	Substance no. 2422 Substance no. 2423 Substance no. 2425 Substance no. 2426 Substance no. 2427 Substance no. 2428 Substance no. 2429 Substance no. 2430 Substance no. 1594
Iso-Butane 75-28-5	Substance no. 2422 Substance no. 2423 Substance no. 2425 Substance no. 2426 Substance no. 2427 Substance no. 2428 Substance no. 2429 Substance no. 2430 Substance no. 1040
Sodium nitrite 7632-00-0	Substance no. 2258

U.S. TSCA: One or more components of this product is not listed on the TSCA Inventory.
Canadian Inventory: One or more components of this product is not listed on the Canadian DSL or NDSL Inventory.

Consumer Product Safety Improvement Act of 2008 General Conformity Certification

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product container.

16. OTHER INFORMATION

General Notes:
Disclaimer: Do not allow undiluted material or large quantities to reach groundwater, bodies of water or sewer system. The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.