

# MATERIAL SAFETY DATA SHEET

Trade Name: Johnsen's Gas Treatment 7 oz  
MSDS NO. 4679-8  
Revision Date: 05/25/2007  
Date Printed: 01/20/2009

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade Name: Johnsen's Gas Treatment 7 oz  
Chemical Family: PETROLEUM DISTILLATE  
Synonyms: None  
Emergency Telephone (24 hr.): CHEMTREC 1-800-424-9300  
Supplier: Technical Chemical Company, P.O. Box 139, Cleburne, Texas 76033

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight %	OSHA TWA	OSHA STEL	OSHA SKIN
Solvent naphtha (petroleum), light aromatic 64742-95-6	.1-10	Not Listed	Not Listed	Not Listed
400/500 Base Solvent 64742-47-8	90-100	500 ppm	Not Listed	Not Listed

Component	Weight %	OSHA Z PEL	OSHA Z TWA	OSHA Z Ceiling
Solvent naphtha (petroleum), light aromatic 64742-95-6	.1-10	Not Listed	Not Listed	Not Listed
400/500 Base Solvent 64742-47-8	90-100	500 ppm	500 ppm	Not Listed

Component	ACGIH TLV TWA	ACGIH TLV STEL	ACGIH TLV Ceiling
Solvent naphtha (petroleum), light aromatic 64742-95-6	Not Listed	Not Listed	Not Listed
400/500 Base Solvent 64742-47-8	Not Listed	Not Listed	Not Listed

## 3. HAZARDS IDENTIFICATION

**Emergency Overview:** Warning! May cause delayed lung injury. Combustible Liquid and Vapor. Exposure to vapors can cause central nervous system depression, drowsiness, weakness, headache, dizziness, and nausea. Harmful if inhaled. Avoid breathing vapors. Avoid contact with skin and eyes. Keep away from heat, sparks, and flame.

**HMIS Classification:** Health: 2 Flammability: 2 Physical Hazard: 0  
**NFPA Rating:** Health: 2 Flammability: 2 Reactivity: 0

## 4. FIRST AID MEASURES

**Eye Contact:** In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.

**Ingestion:** If swallowed, do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person. If victim is conscious and alert, give 1-2 glasses of water to drink. If vomiting occurs, keep head lower than hips to prevent aspiration.

**Inhalation:** If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

**Skin Contact:** Remove contaminated clothing and shoes, and launder before reuse. Wash with soap and water. If irritation or rash develops, obtain medical assistance.

## 5. FIRE FIGHTING MEASURES

Flammable Properties

# MATERIAL SAFETY DATA SHEET

Trade Name: Johnsen's Gas Treatment 7 oz  
MSDS NO. 4679-8  
Revision Date: 05/25/2007  
Date Printed: 01/20/2009

## 5. FIRE FIGHTING MEASURES

Flash Point F(°C): >155 F  
Flash Point Method: TAG Closed Cup  
Flammable Limits in Air - Lower (%): .7 vol %  
Flammable Limits in Air - Upper (%): 6 vol %  
Autoignition Temperature F(°C): >550 F  
Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam. Use water spray to keep containers cool that are exposed to heat or flames. Water stream may spread fire.

**Protection Of Fire-Fighters:**  
**Special Fire-Fighting Procedures:** Wear approved positive-pressure self-contained breathing apparatus and protective clothing.  
**Hazardous Combustion Products:** Oxides of Carbon. Fumes and Smoke. Oxides of Nitrogen.  
**Aerosol Comments:** Not Applicable

## 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** Wear appropriate protective clothing and equipment to prevent skin and eye contact.  
**Spill Procedures:** Sweep or scrape up material and place in a suitable clean, dry container for disposal by approved methods.  
**Action to be taken if material is released or spilled:** Remove sources of ignition. Increase area ventilation. Leaking containers should be removed to an isolated, well-ventilated area and transferred to other suitable containers.  
**Environmental Precautions:** Do not allow to enter sanitary drains, sewer or surface and subsurface waters.

## 7. HANDLING AND STORAGE

**Handling and Storage:** Keep containers tightly closed when not in use. Keep away from heat and open flame. Wash thoroughly after handling. Use only with adequate ventilation. Avoid extreme temperatures. Wash hands before eating, drinking, chewing gum, using tobacco or using the toilet.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering Controls:** Exhaust ventilation. Showers. Eyewash stations.  
**Eyes:** Wear safety glasses or goggles to protect against exposure. Chemical goggles; also wear a face shield if splashing hazard exists.  
**Skin Protection:** Nitrile coated apron or clothing. Neoprene coated apron or clothing. Avoid skin contact. Wear protective clothing and gloves.  
**Respiratory Protection:** Use an approved NIOSH organic vapor respirator below the TLV. If TLV is exceeded or overexposure is likely, use positive pressure or self contained breathing apparatus.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Colorless to light yellow liquid  
**Odor:** KEROSENE  
**pH Value:** Not Determined  
**Vapor Pressure:** .00386 psia @ 68F  
**Vapor Density (Air=1):** 6  
**Boiling Point (°F):** >400F  
**Melting/Freezing Point:** 25F  
**Solubility in Water:** NEGLIGIBLE  
**Bulk Density at 20°C:** Not Determined  
**Molecular Weight:** Mixture  
**Specific Gravity (H2O=1):** .803 @ 70F  
**Viscosity:** >1.7 cst @ 40C  
**Evaporation Rate:** Not Determined  
**VOC Content(%):** 2.71 (CARB Method 310)  
**Decomposition Temperature:** Not Known

## 10. STABILITY AND REACTIVITY

**Chemical Stability:** Stable under normal conditions of handling, use and transportation.  
**Conditions to Avoid:** Keep away from heat, sparks and flame. Do not expose to heat or store at temperatures above 120 F.  
**Materials to Avoid:** Strong oxidizing agents.  
**Hazardous Decomposition Products:** Carbon monoxide and other asphixiates.

# MATERIAL SAFETY DATA SHEET

Trade Name: Johnsen's Gas Treatment 7 oz  
MSDS NO. 4679-8  
Revision Date: 05/25/2007  
Date Printed: 01/20/2009

## 10. STABILITY AND REACTIVITY

Hazardous Polymerization: WILL NOT OCCUR

## 11. TOXICOLOGICAL INFORMATION

Toxicological Data:

Component	Route	Species	Dose
Solvent naphtha (petroleum), light aromatic 64742-95-6	Oral	Rats	LD50 8400 mg/kg
400/500 Base Solvent 64742-47-8	Inhalation	Rats	Not known.

Carcinogenicity:

Component	IARC	NTP	OSHA
Solvent naphtha (petroleum), light aromatic 64742-95-6	Not Listed	Not Listed	Not Listed
400/500 Base Solvent 64742-47-8	Not Listed	Not Listed	Not Listed

## 12. ECOLOGICAL INFORMATION

**Remarks:** Ecological testing has not been conducted on this product.

## 13. DISPOSAL CONSIDERATION

**Waste Classification:** Not determined.  
**Waste Management:** Recovery and reuse, rather than disposal, should be the ultimate goal of handling efforts.  
**Disposal Method:** Disposal should be made in accordance with federal, state and local regulations.

## 14. TRANSPORTATION INFORMATION

**U.S. DOT:**  
Proper Shipping Name: Consumer Commodity  
Hazard Class: ORMD  
UN/NA Number: Not Applicable  
DOT Packing Group: Not Applicable

**IMDG:**  
Proper Shipping Name: Combustible Liquid, nos  
Hazard Class: 3  
Hazard Subclass: Not Determined  
UN No.: 1993  
Packing Group: III  
Marine Pollutant: No

## 15. REGULATORY INFORMATION

US Federal Regulations:

## MATERIAL SAFETY DATA SHEET

Trade Name: Johnsen's Gas Treatment 7 oz  
 MSDS NO. 4679-8  
 Revision Date: 05/25/2007  
 Date Printed 01/20/2009

Component	SARA 313	SARA 302	TPQ	RQ
Solvent naphtha (petroleum), light aromatic 64742-95-6	Not Listed	Not Listed	Not Listed	Not Listed
400/500 Base Solvent 64742-47-8	Not Listed	Not Listed	Not Listed	Not Listed

**SARA 311/312 Hazard Categories:** Immediate/Acute, Delayed/Chronic, Fire

**State Regulations:**

Component	California Prop. 65 Cancer list	California - Prop 65 Developmental Toxicity	California Prop. 65 Reproductive Female	California Prop. 65 Reproductive Male
Solvent naphtha (petroleum), light aromatic 64742-95-6	Not Listed	Not Listed	Not Listed	Not Listed
400/500 Base Solvent 64742-47-8	Not Listed	Not Listed	Not Listed	Not Listed

**U.S. TSCA:** The components of this product are listed on the TSCA Inventory.  
**Canadian Inventory:** The components of this product are listed on the Canadian DSL or NDSL Inventory.

**Consumer Product Safety Improvement Act of 2008 General Conformity Certification**

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product container.

### 16. OTHER INFORMATION

**General Notes:**  
**Disclaimer:** Do not allow undiluted material or large quantities to reach groundwater, bodies of water or sewer system. The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.